PROJECT DESCRIPTION

GENERAL

This project involves the reconstruction of the traffic signal at the intersection of US 50 (Ocean Gateway) and Walston Switch Road in Parsonsburg, Maryland. US 50 (Ocean Gateway) is assumed to run in an east—west direction.

Intersection lighting will be provided on signal poles.

II. INTERSECTION OPERATION

1. A proposed NEMA full—traffic actuated signal controller with an Uninterruptible Power Supply housed in a Type "S" base mounted cabinet will be installed. The intersection is to operate using six NEMA phases. The US 50 approaches will operate concurrently with exclusive left turn phasing for the offset left turn lanes. Walston Switch Road will operate with split phasing.

Signal pre-emption phases will be provided for each direction of travel. US 50 approaches will hold the through and left turn phases associated with the approach under pre-emption. Walston Switch Road approaches will hold the split phase associated with the approach under pre-emption.

NOTES

- For final pavement markings, refer to the pavement marking plans, as applicable; other than those detailed on the plan. All pavement markings shall be installed in accordance with Administration standards.
- 2. The contractor shall be responsible for terminating all signal cable to the appropriate terminals and properly labeling each cable.
- All traffic signal foundations shall be installed at the final sidewalk or curb grade for closed sections, highest roadway profile grade for open sections, to meet clearances as specified in the appropriate 800 series Standard Plates. The contractor shall verify ultimate grades prior to the installation of all signal equipment.
- All underground and overhead utilities shown on these plans are schematic only and may not be complete. The Contractor shall be responsible for notifying Miss Utility prior to construction so that all utilities may be located in the field. If the Contractor perceives that a conflict between the utilities and the traffic signal will occur, the Contractor shall notify the Project Engineer immediately so that the conflict may be resolved.
- The contractor shall maintain the continuous operation of all interconnect, vehicular, pedestrian detectors, and lighting devices. If any device is damaged by the contractor, it shall be repaired within 72 hours by the contractor at no cost to the Administration after notification by the Engineer.
- All proposed luminaires shall be supplied with a photocell.
- Upon completion of this project, the contractor shall notify Mr. Robert Snyder to

arrange for the phone line installation. The contractor shall provide Mr. Snyder with the nearest street address, zip code and telephone number.								
CONTACTS								
DISTRICT MR. DONNIE L. DREWER DISTRICT ENGINEER 410-677-4006		OFFICE OF TRAFFIC AND MS. CORREN JOHNSON CHIEF, TRAFFIC OPERATIO 410-787-7630						
MR. KENNETH CIMINO ASSISTANT DISTRICT ENGINEER - TRAFFIC 410-677-4040		MR. ROBERT SNYDER ASSISTANT DIVISION CHIEF, TRAFFIC OPERATIONS 410-787-7630						
MR. BRUCE W. POOLE ASSISTANT DISTRICT ENGINEER — UTILITIES 410-677-4082		MR. ED RODENHIZER CHIEF SIGNAL OPERATIONS 410—787—7650						
MR. GREG HOLSEY ASSISTANT DISTRICT ENGINEER — CONSTRUCTION 410—677—4020		MR. EUGENE BAILEY CHIEF SIGN OPERATIONS 410-787-7670						
MR. WAYNE WEICHMAN ASSISTANT DISTRICT ENGINEER — MAINTENANCE 410—677—4010		MR. MIKE STOCKER SUPPLY OFFICER IV (SIGNAL SHOP WAREHOUSE) 410-787-7668						
EQUIPMENT LIST								
A. EQUIPMENT TO BE FURNISHED BY TH	E ADMINISTRATION							
CAT CODE	DESCRIPTION		UNITS	QUANTITY				

410-677		HEF SIGN OPERATIONS 0-787-7670					
	T DISTRICT ENGINEER — MAINTENANCE SU	R. MIKE STOCKER JPPLY OFFICER IV (SIGNAL 0—787—7668	SHOP V	VAREHOUSE)			
EQUIPMENT LIST							
A. EQUIPMENT TO BE FURNISHED BY THE ADMINISTRATION							
CAT CODE 900000	DESCRIPTION CONTROLLER CABINET, SIZE "S" WITH CONTROLLER INTERFACE FOR 1-8 CAMERAS	& VIDEO DETECTION	INITS EA	QUANTITY 1			
900000	UPS EQUIPMENT FOR "S" CABINET		EA	1			
973023	SHEET ALUMINUM SIGNS CONSISTING OF:		SF	148			
	D-3(1) (96"X16")		EA	2 2			
	R3—2 (30"X30") R3—5(L) (30"X36")		EA	2			
	R3-5(L) MOD (30"X36")		EA EA	5 1			
	R3-6(L) (30"X36")		EA	4			
•	M1-5(4) (78"X36")		EA	ż			
B. EQUIPMENT TO BE FURNISHED AND/OR INSTALLED BY CONTRACTOR							
CAT CODE	DESCRIPTION	, U	INITS	QUANTITY			
203030	TEST PIT EXCAVATION		CY	4			
585625	24 INCH WHITE PREFORMED THERMOPLASTIC PAVEMI	ENT MARKING LINES	LF	210			
800000	DISCONNECT, PULLBACK & REROUTE CABLES		LF	1025			
800000	REMOVE AND DISPOSE OF EXISTING SIGNAL EQUIPMI		LS	1			
800000 800000	FURNISH AND INSTALL SHA COBRA HEAD LED LUMINA IP-BASED VIDEO TRAFFIC DETECTION CAMERAS	MRE	EΑ	4			
801004	CONCRETE FOR SIGNAL FOUNDATION		EA CY	4 17			
802501	NO. 6 AWG STRANDED BARE COPPER GROUND WIRE		LF	1000			
805115	3 INCH SCHEDULE 80 RIGID PVC CONDUIT-BORED		LF	160			
805118	4 INCH SCHEDULE 80 RIGID PVC CONDUIT-BORED		LF	715			
805125	2 INCH SCHEDULE 80 RIGID PVC CONDUIT-TRENCHED)	LF	270			
805135	3 INCH SCHEDULE 80 RIGID PVC CONDUIT-TRENCHED		LF	835			
805140	4 INCH SCHEDULE 80 RIGID PVC CONDUIT-TRENCHED)	LF	660			
807500	EMBEDDED METERED SERVICE PEDESTAL	/ 	EA	1			
810022 810605	ELECTRICAL CABLE 1—CONDUCTOR NO. 8 AWG—THHN		LF	35			
811001	NONINVASIVE DETECTOR, 1000 FOOT LEAD IN CABL FURNISH AND INSTALL ELECTRICAL HANDHOLE	<u>r</u>	EA	4			
813015	INSTALL OVERHEAD SIGN		E A SF	15 148			
2.20.0	TOTALE OVERTIEND STORT		اد	I TO			

